

## High-Speed, Portable BGAN Terminal

### Raising the BGAN bar

EXPLORER 710 is a portable satellite terminal set to usher in a new era in the world of BGAN by setting new standards for size, speed and features.

### Smallest and Lightest

The smallest full Class 1 BGAN terminal positioned to support broadcasters by enhancing the quality of mobile outside broadcasting.



### The EXPLORER 710 High-Speed, Portable BGAN Terminal

- On-demand, guaranteed streaming rates up to 650 kbps (HDR)
- Integrates with cellular-data technology to utilize least-cost-based routing
- Smart phone integration for phone calls (via internal SIP server) and Internet (via internal WLAN)
- Plug-&-play bonding - simply connect two EXPLORER-710 units and nearly double the streaming rates
- A low-end VSAT capability in a portable BGAN form

### Fastest ever BGAN

The first and only BGAN terminal to support the full High Data Rate on-demand streaming service from Inmarsat. With speeds averaging 650 kbps, the EXPLORER 710 sets a new standard for mobile video newsgathering.

Double the speed with Plug & Play bonding; simply connect two EXPLORER 710 terminals with an ethernet cable and achieve streaming rates over 1 Mbps.

### Smart and Easy

EXPLORER 710 introduces smart devices to the world of BGAN, enabling users to connect their own smart phone for terminal control, voice calls and connectivity. The EXPLORER Connect App with a SIP softphone is available on Android and IOS.

Other features include a USB host interface, hot-swappable batteries, a large easy-to-use LED display and multiple interfaces to support a wide range of applications.

# EXPLORER 710

# EXPLORER 710

High-Speed, Portable BGAN Terminal

# COBHAM



## Package Includes:

- EXPLORER 710 Transceiver & Antenna
- Rechargeable lithium ion battery
- Antenna cable
- 2m ISDN/LAN cable
- 115/230VAC power supply
- Quick start guide

## Specifications

### Dimensions

Total H / W / D: 332 / 279 / 54 mm  
13.07 / 10.98 / 2.13 inches

### Total weight:

Antenna: 1.9 kg / 4.2 lbs  
Transceiver (incl. battery): 1.6 kg / 3.5 lbs

### Global Services

Voice: 4 kbps AMBE+2  
Premium voice: 3.1 kHz audio, 64 kbps  
Standard IP: Up to 492 kbps  
Streaming IP: 32, 64, 128 kbps  
(256 kbps & BGAN X-Stream)  
High Data Rate Streaming: Min. 600 kbps  
ISDN: Min. 300 kbps (Half-channel HDR)  
UDI 64 kbps / RDI 56 kbps  
SMS: Not supported

**Inmarsat frequencies:** 1518.0 - 1525.0 MHz (Rx) (EMEA)  
1525.0 - 1559.0 MHz (Rx)  
1626.5 - 1660.5 MHz (Tx)  
1668.0 - 1675.0 MHz (Tx) (EMEA)

**EIRP:** 20dBW ±1dB

**User Interface:** PMOLED Display, 5 navigation keys, Audio and LCD pointing aids and LED indicator, Compass

**Languages:** UK, FR, DE, ES, RU and CN

**Approvals:** Inmarsat Class 1 Type Approval at launch CE & FCC at launch. Other approvals TBC

## Interfaces

### 1 x Analogue RJ-11 phone/fax interfaces

### 2 x LAN (RJ-45) interface

Power over Ethernet: PoE Cl. 2 on one RJ-45 interface  
Max. cable length: 100m / 328ft (Cat5 UTP)

### 1 x USB host interface

2.0 (host), Charging up to 2A

### 1 x ISDN interface

Connector type: RJ-45  
Max. units per port: 8, max. total power supplied 1W

### 1 x Transceiver / Antenna interface

Connector type: TNC-TNC  
Max. cable loss: 1.4 / 20dB @ 1.5GHz

### 1 x BGAN SIM-Card slots

### WLAN Access Point

Standard: IEEE 802.11 b/g

## Environmental conditions

### Temperature

Operational (ambient): -25°C to +55°C / -13°F to +131°F  
Storage (excl. battery): -40°C to +80°C / -40°F to +176°F

### Battery storage temperature

1 month: 20°C to +60°C / -4°F to +140°F  
3 months: -20°C to +45°C / -4°F to +113°F  
1 year: -20°C to +20°C / -4°F to +68°F

**Water and dust:** Transceiver: IP52 / Antenna: IP66

**Relative humidity:** 95% non-condensing at +40°C / +104°F

## Other features

Built-in SIP server  
Embedded Webservice  
Advanced Router with admin control  
Wireless Access Point  
Battery hot-swap and Built-in BGAN bonding  
Remote activation and remote management

### EXPLORER Connect App for IOS and Android:

Includes a SIP Softphone, Terminal Access to control your BGAN and Pointing Assistance.

### EXPLORER Cellular Modem for USB:

With the EXPLORER LTE Modem you can connect local cellular networks and use the EXPLORER 510 as wireless router for all your devices.

## Accessories

403720B-100	EXPLORER 710 Antenna
403686G	Lithium Ion Battery
403720B-010	Battery Hot Swap Cable
403682P	100-240V AC/DC Power Supply
403650A-009	Car Charger Cable
403670A-00500	IP Handset incl. Cradle
403650A-921	Pole Mount Kit
403720B-942	10m Antenna Cable
403720B-945	30m Antenna Cable
403720B-947	50m Antenna Cable EXPLORER
403756A-0500	Cellular USB Modem

## Product number

403720B-00500 EXPLORER 710 Terminal

## Power

**DC input range:** 10-32VDC

### Power consumption

Intelligent Power Management 65W (max.)

### AC/DC power supply

Input: 100-240VAC, 47-63Hz,  
Output: 65W 19VDC  
Connector type: 2.5 / 5.5 mm power jack

## Battery:

Lithium ion, rechargeable  
Stand-by time: 24 hours (to be confirmed)  
Transmit time, max.: 2h30m @ 144 kbps  
(25°C / 77°F) 1h30m @ 650 kbps  
Receive time, max.: 3h30m @ 492 kbps



[sales@networkinv.com](mailto:sales@networkinv.com)

US: +1.954.973.3100  
CA: +1.403.287.5000  
EU: +31.40.295.3001  
UK: +44.20.8286.6768  
SG: +65.6274.0811  
AU: +61.1300.140.150  
SE: +46.8.7652670

[www.networkinv.com](http://www.networkinv.com)

### Americas

Canada  
United States

### Asia/Pacific

Singapore  
Australia

### Europe

Netherlands  
United Kingdom  
Sweden

v2032017us